



Technische eigenschappen

| Profielplaatype | Staaldikte [mm] | Gewicht [kg/m ²] | I _{eff} [cm ⁴ /m] | Gewicht Perfo[kg/m ²] | I _{eff} [cm ⁴ /m] |
|-----------------|-----------------|------------------------------|---------------------------------------|-----------------------------------|---------------------------------------|
| 100/600 | 0,75 | 9 | 91 | 7,5 | 65 |
| | 0,88 | 10,6 | 126 | 8,8 | 81 |
| | 1,00 | 11,9 | 141 | 9,9 | 96 |
| | 1,25 | 14,8 | 177 | 12,3 | 121 |
| | 1,50 | 17,8 | 214 | 14,8 | 146 |

| | |
|----------------|---------------|
| Staalkwaliteit | S320GD |
| Coatings | Verzinkt Z275 |
| Optioneel | Geperforeerd |

| | | |
|-------------|-----------|----------------|
| Afmetingen | Standaard | 1.800 - 15.000 |
| Lengte [mm] | Minimaal | 1.800 |
| | Maximaal | 22.000 |

| | | |
|------------|-------------------------|----------|
| Verpakking | Max. aantal per pakket | 22 stuks |
| | Max. gewicht per pakket | - kg |

Certificaten

